

SMART BUILDING TECHNOLOGY

frogDisplay

The 3,5" frogblue "Smartphone" withTouchscreen-Control and WLAN-Gateway for the recessed mounting (230 V~). Featuring integrated Proximity Sensor, Brightness Sensor, Microphone, Loudspeaker, Temperature Sensor, Time based Buffering.





Technical Data

Category	frogDisplay CU-Dis-A.01 Surface mounted (in device socket)		
Article designation Article number Type of assembly			
		Functions and power	
		Inputs	2; for connecting potential-free contacts (switches, buttons, relays
Outputs	0		
Microphone	Yes		
Loudspeaker	Yes		
Proximity sensor	Yes, maximum range 1 metre		
Room temperature sensor	Yes		
Light sensor	Yes		
Door opening function	Yes		
Integrated logic module	Yes		
Integrated configuration backup	Yes		
Comfort and timer functions	Yes		
Bluetooth, WLAN and KNX gateways			

frogDisplay

Dimensions and weight

Dimensions (L \times B \times H):

 $81 \times 81 \times 12$ mm (overall height 45 mm)


frogblue_Data_EN_5-20_CU-Dis-A.01 06.20

Electrical equipment may be installed and fitted only by

Subject to change.

qualified electricians.

Weight: 130 g



Connection example:

Display	
Type	TFT QVGA
Diagonal	88 mm (3.5")
Resolution	320 x 240 px
Electricity supply	
Mains voltage	AC 110-240 V ~
Mains frequency	50 / 60 Hz
Typical Power consumption	3 Watts
Network	
WLAN	2.4 GHz 802.11 b/g/n
Frequency range	2400-2483.5 MHz maximum 13.2dBm
Bluetooth	Bluetooth 4.2 Low Energy
Frequency range	2400-2483.5 MHz maximum 4.5dBm
Typical radio open field range	30 metres
Operation and storage	
Ambient temperature	-25° to +45 °C
Storage temperature	-25° to +70 °C
Air humidity (during operation)	(Non-condensing)
Power connection	
Connection type	Spring-type terminal (single wire)
Wire cross section	1-1.5 mm ² /0.2-0.5 mm ² (rigid conductor recommended)
Maximum cable length of the inputs ø 0.5 mm ²	100 m
Stripping length	8 mm (1-1.5 mm²) / 6 mm (0.2-0.5 mm²)
Packaging	
Packaging size	1 unit
EAN 1 unit	4260578530262
Packaging dimensions (L \times W \times H) 1 unit	$140 \times 130 \times 60 \text{ mm}$
Weight including packaging 1 unit	220 g

Further information

www.frogblue.com.

